**PROSUPPORT PROFILE T & N** is a profile for the protection and finishing of the external edge of raised floors in ceramic, wood and composite materials. The vertical section of the profiles features a specially designed fins that create a dovetail cladding system. This dovetail cladding system allows for the adhesive used to fix the covering to also mechanically bond to the profiles. The profile is also available with a decorative edge of 2 cm

## **PROSUPPORT** PROFILE T & N

VARNISHED ALUMINIUM NATURAL ALUMINIUM



### PROSUPPORT PROFILE T - VARNISHED ALUMINIUM

bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm	h mm	
PSPRPT 20AL	177,7x81,5	60	

#### COLOURS (EMBOSSED)

<b>GF</b> - Grey <b>(7038)</b>	A - Anthracite grey - (no RAL)

#### \* ON DEMAND (EMBOSSED)





# PROSUPPORT PROFILE N - NATURAL ALUMINIUM

bar length 2,7 mm - pack. 20 1 cs - 34 mm			
Article	H mm	L	

60

156.5


#### COLOURS



PSPRP 15560AL

### LAYING INSTRUCTIONS

1. Choose "PROSUPPORT PROFILE" desired model. 2. Cut "PROSUPPORT PROFILE" to the desired lenght and put on the supports and aligning. 3. Lay the floor by adjusting the height of the supports until completely leveling. 4. Cut the tiles of the correct size to close the perimeters of the floating floor. 5. Fix on the vertical surface of the profile the tiles using a suitable adhesive.







PROSUPPORT SYSTEM A&B Perimeter profile to protect and finish the outer edge of raised floors of different types, ceramic, wood, stone etc. The **PROSUPPORT PROFILE** A consists in an "L"-shaped horizontal flat base to insert and anchor above the **PROSUPPORT** Self-levelling head and a vertical visible part to insert in the vertical "L"-shaped element (as indicated in the drawing). **Use:** Perimeter profile to protect and finish the outer edge of raised floors of different types, ceramic, wood, marble etc. The **PROSUPPORT** 

PROFILE consists in an "L"-shaped horizontal flat base to insert and anchor above the PROSUPPORT Self-levelling head and a vertical visible part to insert in the vertical "L"-shaped element (as indicated in the drawing)

# **PROSUPPORT** PROFILE A & B

VARNISHED ALUMINIUM, NATURAL ALUMINIUM




PUNCHED AND PERFORATED PROSUPPORT A NATURAL ALLIMINIUM - length 2.7 lm - nack 20 Pcs

THE STATE OF THE S	. 10118011 2,7	pacit. 20 i Co	
Article	LxH		
BPPSAN 15015	150 X 15		
BPPSAN 15020	150 X 20		
BPPSAN 15025	150 X 25		

#### COLOURS





**TOP PROFILE PROSUPPORT B - VARNISHED ALUMINIUM** length 2.7 lm

· ·		
Article	H1	
PFPSAL 1060 (Pack. 20 Pcs)	60	
<b>PFPSAL 1080</b> (Pack. 10 Pcs)	80	
<b>PFPSAL 10100</b> (Pack. 10 Pcs)	100	

#### COLOURS (EMBOSSED)



#### \* ON DEMAND (EMBOSSED)



