


## MAGNET KIT



**MAGNET KIT - 4 magnets and 4 plates**  
for ceramic inspection panel - packs of **10 kits** - price for **1 Kit**

Article	€/KIT
KMD	

## SCISSORS FOR PVC PROFILES



**SCISSORS**  
for cutting PVC profiles

Article	€/Pc
FTPP	

## PROECOFON

EXPANDED POLYETHYLENE CLOSED - CELL

**PROECOFON** is a roll of closed-cell polyethylene used as edging between the wall and screed or where there are expansion joints. It should be used in all floor-laying work to ensure long life of the floor.




### CLOSED-CELL EXPANDED POLYETHYLENE

Article	Thick. x H mm	lm/roll	€/lm	€/Roll
PEF 550A	5 X 50	25		
PEFPU 510A	5 X 10	2,7		
PEF 5100A	5 X 100	100		

For perimeter areas and joints.  
PEFPU 510A for Proterrace Drain Drip

### EXEMPLE OF LAYING



## PROBAND FIX

MONOCOMPONENT WATERPROFF SEALANT



### SEALANT MONOCOMPONENT WATERPROOF

Pack of **12** cartridges

Article	Cartridge lm	€/Pc	€/Pack.
PRBFXB	290		
PRBFXG	290		

### DISPENSING GUN FOR SEALANT CARTRIDGES

Article	Pc/Pack	€/Pc
PRBFXGUN	1	

### SEALANT MONOCOMPONENT WATERPROOF CARTRIDGE

Pack of **12** cartridges

Article	Cartridge lm	€/Pc	€/Pack.
PRBFXUB	600		
PRBFXUG	600		

### COLOURS

B - White	G - Grey

### Technical data:

Appearance:	white or gray thixotropic paste
Temperature range for application:	+ 5 °C / + 40 °C
Temperature range:	- 40 °C / + 90 °C
Curing:	≈ 2 mm / 24 h
Commissioning:	≈ 7 days

### Suggestions for the installation:

In general cementitious support must be free from dust, oil and grease, dry and free from any visible moisture, free of loose or imperfectly anchored parts such as residual traces of cement, lime and paint, which must be totally removed. In case of contact with eyes, rinse immediately with water and seek medical advice. Avoid contact with skin and keep out of reach of children.

### • Use

Balconies, terraces, bathrooms, kitchens, saunas, swimming pools and exterior surfaces of any size.

### • Don't use

On bitumen membranes.  
To seal proband with PRODESO®.

## PROPOLISH

WHITE CREAM - BASED SURFACTANTS  
SUITABLE FOR CLEANING

White cream - based surfactants, amines and inert powder, suitable for cleaning, degreasing and polishing of stainless steel surfaces and opaque/matt brass. The product, ready to use, does not contain acids and alkalis and do not leave marks after use. It does not emit harmful substances



Article	Pack. g.	Pcs/Pack	€/Pc	€/Pack.
PRLISH	250	6		

## PROCARE CLEAN

CLEANING SPRAY

Cleaning spray ready to use suitable for cleaning of stainless steel, brass and aluminum profiles, from residual surface oxide and limestone. The product deposit a protective film that prevents the deposit of limestone and soap residues. Its periodic use allows to obtain bright and cleaner surfaces for long period. Suitable also for glasses, mirrors and bathroom fittings.



Article	Pack. lm	Pcs/Pack.	€/Pc	€/Pack.
PRCLEAN	750	6		