PROTERMINAL INT is a profile in anodized and polished aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section and the availability in four different finishes make **PROTERMINAL INT** a much sought-after profile that allows an elegant workmanlike application.

PROTERMINAL

ANODIZED AND POLISHED ALUMINIUM



ANODIZED ALUMINIUM (silver - titanium) thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

| bei leight - , in pack is is in | | | | | | |
|--|-----------|------|--|--|--|--|
| | Article | Hmm | | | | |
| | PTIAA 08 | 8 | | | | |
| | PTIAA 10 | 10 | | | | |
| | PTIAA 125 | 12,5 | | | | |
| | PTIAT 08 | 8 | | | | |
| | PTIAT 10 | 10 | | | | |
| | PTIAT 125 | 12,5 | | | | |

INTERNAL, EXTERNAL, THREE-WAYS JOINTS ANODIZED POLISHED ALUMINIUM - pack. 3 Pcs

Article RIPTI ... 08 - 10 - 125/3 REPTI ... 08 - 10 - 125/3

RTPIT ... 08 - 10 - 125/3

COLOURS

| ANODIZED | | POLISHED | | |
|----------------------------|------------------------------|----------------------------|------------------------------|--|
| | | | | |
| AA - Anodized silver alum. | AT - Anodized titanium alum. | BC - Polished chrome alum. | BT - Polished titanium alum. | |



POLISHED ALUMINIUM (chrome - titanium) thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

| H mm | | |
|------|----------------------------|----------------------------|
| 8 | | |
| 10 | | |
| 12,5 | | |
| 8 | | |
| 10 | | |
| 12,5 | | |
| | 8 10 12,5 8 10 | 8 10 12,5 8 10 |

INTERNAL CORNER **3 WAYS JOINT** EXTERNAL CORNER RTPIT ... 08 - 10 - 125 RIPTI ... 08 - 10 - 125 REPTI ... 08 - 10 - 125

On demand may be realised in other finishes of the colour chart. Contact our customer service for minimal quantity, timing and price.

8 - 10 12,5 mm PTI ... H 8 - 10 12.5





1. Choose "PROTERMINAL INT" according to the tile thickness and desired finish. 2. Cut "PROTERMINAL INT" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROTERMINAL INT" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.





L Е