PROTERMINAL is a L-shaped profile in chromed and antique brass that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles and also as separation profile for floor and wall coverings. Its particular section and elegance make PROJOLLY a much sought-after profile that allows a workmanlike application.

PROTERMINAL is a L-shaped profile in natural and anodized aluminium that can be applied on external corners

of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles and also as separation profile for floor and wall coverings. Its particular section and the availability in six different finishes make **PROTERMINAL** a much sought-after profile

PROTERMINAL

CHROMED BRASS, BRUSHED BRASS AND ANTIQUE BRASS



CHROMED BRASS thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm	
PTOC 06	6	
PTOC 08	8	
PTOC 10	10	
PTOC 125	12,5	

COLOURS



BRUSHED BRASS thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	H mm	
PTOS 06	6	
PTOS 08	8	
PTOS 10	10	
PTOS 125	12,5	

ANTIQUE BRASS thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

	Article	H mm	
③	PTOB 06	6	
	PTOB 08	8	
	PTOB 10	10	
	PTOB 125	12,5	

INSTRUCTIONS FOR LAYING METHODS

1. Choose "PROTERMINAL" according to the tile thickness. 2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROTERMINAL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

PT... 08

H 8 mm

PT... 10

H 10 mm

EXEMPLES OF LAYING

PROTERMINAL

NATURAL AND ANODIZED ALUMINIUM



ANODIZED ALUMINIUM (gold - silver) thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

that allows a workmanlike application.

501 1011501 272 1111 pacini 10 11		
Article	H mm	
PTAA 03	3	
PTAA 045	4,5	
PTAA 06	6	
PTAA 08	8	
PTAA 10	10	
PTAA 11	11	
PTAA 125	12,5	
PTAA 15	15	
PTAA 20	20	
PTAO 03	3	
PTAO 045	4,5	
PTAO 06	6	
PTAO 08	8	
PTAO 10	10	
PTAO 11	11	
PTAO 125	12,5	

COLOURS

= News 2023

ANODIZED			
AA - Anodized silver alum.	AO - Anod. gold alum.	NE - Anodized black alum.	
AT - Anodized titanium alum.	AR - Anodized copper alum.	AB - Anodized bronze	
BRA - Anod. antique bronze			



ANODIZED ALUMINIUM (black-titanium-copper-bronze- antique bronze) thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

	0 ,		
	Article	H mm	
PTNE 08		8	
PTNE 10		10	
PTNE 125		12,5	
PTAT 08		8	
PTAT 10		10	
PTAT 11		11	
PTAT 125		12,5	
PTAR 08		8	
PTAR 10		10	
PTAR 125		12,5	
PTAB 08		8	
PTAB 10		10	
PTAB 125		12,5	
PTBRA 10		10	
PTBRA 12	5	12,5	


NATURAL ALUMINIUM

bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	H mm	
PTAN 03	3	
PTAN 045	4,5	
COLOURS		

AN - Natural aluminium

On demand may be realised in other finishes of the colour chart.
Contact our customer service for minimal quantity, timing and price.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROTERMINAL" according to the tile thickness and desired finish. 2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROTERMINAL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

