It is an uncoupling and waterproofing membrane for problematic substrates, balconies, terraces and horizontal surfaces of any size without expansion joints in the screed before the laying of ceramic and natural stone. **PRODESO®** ensures the laying of the flooring and the waterproofing of the substrate also in case of old tiles, on cracked and not perfectly cured substrates, and therefore with possible vapour pressure.

PRODESO® MEMBRANE

UNCOUPLING & WATERPROOFING MEMBRANE

PRODESO® MEMBRANE

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet		
PDES 3530/EN	1	30	3,5	8		
PDES 3505/EN	1	5	3,5	56		

WHY USE PRODESO® MEMBRANE SYSTEM

Time Efficient: PRODESO® Membrane reduces drastically the installation times because from the installation of the membrane up to the laying of flooring you can work without interruption.

Flexible: it is suitable for every types of subfloor including very large surfaces both indoor and outdoor.

Safe: it is suitable for substrates with cracks as it does not transmit tension of the substrate to the tile coverings and vice versa. It is also suitable on substrates not perfectly cured since it allows the vapour management.

WARNINGS

Do not lay tiles with a size less than 5 x 5 cm. The technical and application details can be found in the PRODESO® MEMBRANE SYSTEM brochure. For other informations not described in the brochure PRODESO® MEMBRANE SYSTEM, refer to the technical department.

L 5m

L 30m



PROBAND 150/250 is a waterproofing polyethylene tape with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support

PROBAND 150/250

ROLLS IN HDPE AND PP

PROBAND 150/250

Article	H roll (m)	L roll (m)	Thickness (mm)	Rolls/Pallet		
PRBPE 1507	150	7,5	0,42	16		
PRBPE 1530	150	30	0,42	6		
PRBPE 2530	250	30	0,42	3		

For the indicative consumption of proband koll AB during the installation of the PROBAND, consult the technical data sheet of PROBAND 150/250



AREA OF USE

- Use Terraces, balconies and outside surfaces of any dimension, bathrooms, showers, swimming pools and tanks. To realize waterproofing joints between floor and wall and along two adjacent rolls of PROFOIL, PRODESO® MEMBRANE SYSTEM and PRODESO® HEAT/GRIP SYSTEM
- Don't use On bituminous coverings, over thermal-insulating layer and lightweigh screed. With adhesives containing solvents. WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat. Read the data sheet before applying; in case of special applications call the technical department

Grigolin

RECOMMENDED ADHESIVES FOR THE LAYING OF PRODESO® MEMBRANE (grey color)

LITOKOL

SUPERFLEX K77

POWERFLEX K50 LITOSTONE K99









inde»:

A SIKA COMPANY

FLEXBOND C2S1

FLEXBOND LIGHT C2S1

WETBOND RAPID C2F





GRIGOKOLL TEX

GRIGOKOLL MAX

GRIGOKOLL VELOX









CERAM 255 STARFLEX

CERAM 255 EASY S1 CERAM 270 MULTIFLOW



ULTRAGRES 440 ULTRAGRES FLEX ULTRAGRES FAST

KRISTAL C2TE

EXTRA C2S1








AZ 59 RAPID MAXI SPECIAL ONE







FORTEM



BENFERFLEX+S1 F.55 CERMONO PLUS F.55 CERFIX F.55 CERMONO RAPIDO **BENFERFLEX + FAST-S1**



EXTRA 30 MAXI ADEFLEX GREEN S1 **EXTRA 30 POWER**



KERAFLEX EASY **ULTRALITE S1 KERAFLEX MAXI S1**