SKIRTING 40 made in anodized, polished and brushed aluminium in height 40 mm. Available with or without adhesive. Superior aesthetic quality and easy to lay, it is ideal for all public and private environments. Can be used with all types of flooring. In order to facilitate and to perfect the laying process, internal and external angles, plugs and junctions are recommended.

Please contact the technical department for informations concerning the skirting bending radius.

SKIRTING 40

ANODIZED, POLISHED, VARNISHED and BRUSHED ALUMINIUM



ANODIZED SILVER ALUMINIUM thermo packed

bar length 2 lm - pack. 40 Pcs - 80 lm				
Article	H mm			
BTAA 40A	40			

"A" at the end of the product code = Item with adhesive

POLISHED TITANIUM ALUMINIUM thermo packed

bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm		
BTBT 40A	40		
BTBT 40	40		
"A" at the end of the product coo	de = Item with	n adhesive	

40

VARNISHED SEMIGLOSSY AND MATT WHITE ALUMINIUM

thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm	
BTA 40-01A	40	
BTA 40-01	40	
BTA 40-01OA	40	
BTA 40-010	40	

"A" at the end of the product code = Item with adhesive



BRUSHED ALUMINIUM (silver-copper-titanium) thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

Article	H mm	
BTBS 40A	40	
BTBS 40	40	
BTRS 40A	40	
BTRS 40	40	
BTTS 40A	40	
BTTS 40	40	

"A" at the end of the product code = Item with adhesive


STONE LINE ALUMINIUM

thermo packed - bar length 2 lm - pack. 40 Pcs - 80 lm

	Article	H mm		
③	BTA 40-SL01A	40		
₃	BTA 40-SL01	40		
③	BTA 40-SL08A	40		
③	BTA 40-SL08	40		
③	BTA 40-SL12A	40		
₃	BTA 40-SL12	40		
	"A" at the end of the product cod	le = Item with	h adhesive	

BT... 40/40A H 40 mm

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "SKIRTING 40" also choose with or without adhesive. 1. Cnoose the "SMITING 4U" also choose with or without adnessive. 2. Cut the profile to the required length, taking care to calculate the width of the inside-outside corner joints. 3. For the self-adhesive version, the surface must be smooth, grease-free and not porous. It is not recommended for plaster and mortar surfaces (version without adhesive is better, using fast-setting acrylic silicone which is suitable for fixing aluminium to mortar - plaster, etc.). 4. Use the corner linking elements-joints and right and left end caps to facilitate laving.

COLOURS

BTAA 40

ANODIZED	POLISHED		BRUSHED		
			ON DEMAND		
AA - Anodized silver alum.	BT - Polished titanium alum.	BS - Brushed silver alum.	RS - Brushed copper alum.	TS - Brushed titanium alum	
SEMIGLOSSY	MATT	STONE LINE			
	ON DEMAND	ON DEMAND	ON DEMAND	ON DEMAND	

(There aren't combinations for the finish alu, RS)

On demand may be realised in other finishes of the colour chart. Contact our customer service for minimum quantity timing and price.

USE PROBAND FIX FOR FIXING THE PROFILE TO THE WALL



CORNERS, END CAPS AND JOINTS

VARNISHED METAL and VARNISHED PLASTIC

* Corners, end caps and joints of the on demand profiles are also on demand

INTERNAL /EXTERNAL CORNER - EDGE COVER - VARNISHED METAL ANODIZED, POLISHED STONE LINE - H 40 MM - L 20 MM

	Article	pack. 2Pcs	pack. 5Pcs
	RIZCTAA 40/		
	REZCTAA 40/		
	RIZCTBT/BS/TS/RS 40/		
	REZCTBT/BS/TS/RS 40/		
	RIZCT01/01O 40/		
	REZCT01/01O 40/		
Э	RIZCTA 40-SL/		
٥	REZCTA 40-SL/		
	Chanse the desired nackaging		

E.g.: RIZCTAA 40/2 (pack. 2 Pcs) - RIZCTAA 40/5 (pack. 5Pcs)

JOINT - EDGE COVER

VARNISHED METAL ANODIZED, POLISHED, STONE LINE

	Article	H mm	
	GIZCTAA 40/	40	
	GIZCTBT/BS/TS/RS 40/	40	
	GIZCT01/01O 40/	40	
<u> </u>	GIZCTA 40-SL/	40	

END CAPS R / L - EDGE COVER - VARNISHED METAL ANODIZED, **POLISHED, STONE LINE** - pack. **4Pcs** (2 R + 2 L) **/ 10Pcs** (5 R + 5 L)

Article	H mm			
TPZCTAA 40/	40			
TPZCTBT/BS/TS/RS 40/	40			
TPZCT01/01O 40/	40			
TPZCTA 40-SL/	40			
	TPZCTAA 40/ TPZCTBT/BS/TS/RS 40/	TPZCTAA 40/ 40 TPZCTBT/BS/TS/RS 40/ 40 TPZCT01/01O 40/ 40	TPZCTAA 40/ 40 TPZCTBT/BS/TS/RS 40/ 40 TPZCT01/01O 40/ 40	TPZCTAA 40/ 40 TPZCTBT/BS/TS/RS 40/ 40 TPZCT01/010 40/ 40







RETCT 40/



RIZCT 40/

GIZCT... 40/..

INTERNAL/EXTERNAL CORNER - EDGE COVER VARNICHED DI ACTIC AMODIZED CILVED DOLICHED AND TITANILIM

THE THE PERSON OF THE PERSON O				
HxL mm	pack. 2Pcs	pack. 5Pcs		
40 x 20				
40 x 20				
40 x 20				
40 x 20				
	HxL mm 40 x 20 40 x 20 40 x 20	HxL mm pack. 2Pcs 40 x 20 40 x 20 40 x 20		

Choose the desired packaging

E.g.: RICTAA 40/2 (pack. 2 Pcs) - RICTAA 40/5 (pack. 5 Pcs)

Available on demand aluminium prewelded internal and external flush corners. Finishing: 01 - 010 - AA - BT - BS - RS - TS. Price to be agreed. Production delay 4/5 weeks.

IOINT - EDGE COVER

VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM

Article	H mm	
GICTAA 40/	40	
GICTBT 40/	40	

END CAPS R / L - EDGE COVER - VARNISHED PLASTIC ANODIZED SILVER, POLISHED AND TITANIUM - pack. 4Pcs (2R+2L) / 10Pcs (5R+5L)

Article	H mm	
TPCTAA 40/	40	
TPCTBT 40/	40	







TPCT... 40/.. joint

Choose the desired packaging. E.g.: TPCTAA 40/2 (pack. 4 Pcs: 2 right + 2 left)

** = Production on demand with minimum quantity of 80 Pcs. Production delay 4/5 weeks. Price to be agreed

