
PROFILE

WITH TRIANGULAR CHAMFER

GREY RIGID PVC

The TRIANGULAR CHAMFER is made in grey rigid PVC in various widths 10-15-20-30 mm and standard length of 2 lm. It is mainly used to chamfer the corners of the concrete pours when making, for example, walls-columns etc. It is strong and easy to lay.



GREY RIGID PVC

bar length 2 lm - pack. 50 Pcs - 100 lm

	Article	Width mm	
P	ST 10	10	
P	ST 15	15	
	0001 11 1		

20.000 lm pallets

GREY RIGID PVC

har length 2 lm - pack 50 Pcs - 100 lm

bar length 2 mm - pack. 30 f C3 - 100 mm				
Article	Width mm			
PST 20	20/22			
PST 30	30/32			

PST 20: 15.000 lm / pallets PST 30: 10.000 lm / pallets



LAYING INSTRUCTIONS

Put the nails into the central part along the profile before pouring the concrete.

ROUNDED TRIANGULAR

CHAMFER FILLET

GREY RIGID PVC





GREY RIGID PVC

bar length 2 lm - pack. 50 Pcs - 100 lm

Article	L mm		
PSD 22	20/22		
PSD 32	30/32		
PST 22: 15 000 lm / pallets			

PST 32: 10.000 lm / pallets







LAYING INSTRUCTIONS

Put the nails into the central part along the profile before pouring

FISHBONE RIBBED JOINT

GREY RIGID PVC







bar length 2 lm - pack. 50 Pcs - 100 lm

Article	H x L mm	
GRP 25	25 X 5	
GRP 45	45 X 5	

GRP 25: 10.000 lm / pallets GRP 45: 5.000 lm / pallets



LAYING INSTRUCTIONS

Laying is very simple: just insert the ribbed joint into the gap deliberately left in the concrete or the screed.

PROFILE

WITH DOUBLE CHAMFER - FOR BALCONIES

GREY RIGID PVC

COLOURS



GREY RIGID PVC

on demand bar length

Article	H mm	
R 117	80	*

LAYING INSTRUCTIONSLaying is very simple: just fix it with nails or clamps in the relative formwork prior to pouring the concrete.

Article	H mm	
R 117	80	*

PROFILE SPECIFICATIONS:

- Chamfer angle 45°Chamfer length 20 mm
- Bar length on demand
- Weight x metre ≈ 2,3 Kg



