
# **PROFILE**

## WITH TRIANGULAR CHAMFER

**GREY RIGID PVC** 

The TRIANGULAR CHAMFER is made in grey rigid PVC in various widths 10-15-20-30 mm and standard length of 2 lm. It is mainly used to chamfer the corners of the concrete pours when making, for example, walls-columns etc. It is strong and easy to lay.



# LAYING INSTRUCTIONS

Put the nails into the central part along the profile before pouring the concrete.

GREY RIGID PVC

bar length 2 lm - pack. 50 Pcs - 100 lm

Article	Width mm	
PST 10	10	
PST 15	15	
20.000 lm pallets		

#### **GREY RIGID PVC**

bar length 2 lm - pack. 50 Pcs - 100 lm

Article	Width mm	
PST 20	20/22	
PST 30	30/32	

PST 20: 15.000 lm / pallets PST 30: 10.000 lm / pallets




# **ROUNDED TRIANGULAR**

30/32 mm

## **CHAMFER FILLET**

**GREY RIGID PVC** 



#### LAYING INSTRUCTIONS

Put the nails into the central part along the profile before pouring the concrete.

#### **GREY RIGID PVC**

bar length 2 lm - pack. 50 Pcs - 100 lm

Article	L mm		
PSD 22	20/22		
PSD 32	30/32		
PST 22: 15 000 lm / nallets			

PST 32: 10.000 lm / pallets

#### COLOURS





# **FISHBONE RIBBED** JOINT

GREY RIGID PVC

## COLOURS



## LAYING INSTRUCTIONS

Laying is very simple: just insert the ribbed joint into the gap deliberately left in the concrete or the screed.

## **GREY RIGID PVC**

bar length 2 lm - pack. 50 Pcs - 100 lm

Article	HxLmm	
GRP 25	25 X 5	
GRP 45	45 X 5	

GRP 25: 10.000 lm / pallets GRP 45: 5.000 lm / pallets



## **PROFILE**

## WITH DOUBLE CHAMFER - FOR BALCONIES

**GREY RIGID PVC** 

## COLOURS



## LAYING INSTRUCTIONS

Laying is very simple: just fix it with nails or clamps in the relative formwork prior to pouring the concrete.

## **GREY RIGID PVC**

on demand har length

Article	H mm	
R 117	80	*

## **PROFILE SPECIFICATIONS:**

- Chamfer angle 45°Chamfer length 20 mm
- Bar length on demand
  Weight x metre ≈ 2,3 Kg



