
The linear spacer **RAPY 100** is strong and resistant, capable of bearing heavy loads thanks to its shape and size. The lateral and horizontal holes allow perfect penetration of the concrete. Upside down it can be used on insulating panels for floors. Spacers may be joined together longitudinally with a simple slot-in system. Ideal for precasting and civil industry, it ensures stability and invisible finish. On demand available in 50 cm cut.

RAPY 100 FOR HEAVY MESH

GREY HD POLYPROPYLENE




GREY HD POLYPROPYLENE

length 1 lm - pack. 80 lm

| Article | H mm | €/lm | €/Pack. |
|---------|------|------|---------|
| PLF 20 | 20 | | |
| PLF 25 | 25 | | |
| PLF 30 | 30 | | |
| | | | |


Maximum weight: 3000 kg a piece (bar lenght: 1lm) equally distributed.



GREY HD POLYPROPYLENE

length 1 lm - pack. 60 lm

| Article | H mm | €/lm | €/Pack. |
|---------|------|------|---------|
| PLF 35 | 35 | | |
| PLF 40 | 40 | | |
| PLF 45 | 45 | | |
| PLF 50 | 50 | | |
| PLF 55 | 55 | | |
| PLF 60 | 60 | | |





Strong and very resistant linear spacer, to be joined lengthwise and have several lengths. The new shape allows to combine high technical performances to a costs optimization.

RAPY 100 ECO

GREY HD POLYPROPYLENE

RAPY 100 ECO

length 1 lm - pack. 64 lm

| Article | H mm | €/lm | €/Pack. |
|---------|------|------|---------|
| PLFE 20 | 20 | | |
| PLFE 25 | 25 | | |
| PLFE 30 | 30 | | |
| PLFE 35 | 35 | | |
| PLFE 40 | 40 | | |
| | | | |

RAPY 100 ECO length 1 lm - pack. 64 lm

| Article | H mm | €/lm | €/Pack. | |
|---------|------|------|---------|---|
| PLFE 45 | 45 | | | + |
| PLFE 50 | 50 | | | × |
| PLFE 55 | 55 | | | + |
| PLFE 60 | 60 | | | × |



spacers

ARTICLES NOT FOR SALE SINGLY

ARTICLES NOT FOR SALE SINGLY

The **RAPY 200** spacer is sturdy, resistant and easy to place. Ideal for reinforced horizontal, vertical and sloped structures. The side and horizontal holes allow it to perfectly penetrate into the concrete. When flipped over, it can be used for insulation panels, floors and precast structures. On demand available at 1 metre.

RAPY 200

GREY HD POLYPROPYLENE

GREY HD POLYPROPYLENE

length 2 lm - pack. 96 lm

| Article | H mm | €/lm | €/Pack. |
|---------|------|------|---------|
| PLF 20R | 20 | | |
| PLF 25R | 25 | | |
| PLF 30R | 30 | | |
| PLF 40R | 40 | | |

Maximum weight: 3000 kg a piece (bar lenght: 2 lm) equally distributed. The spacer is made up of two 1 lm pieces joined together.





Spacer for horizontal use for heavy reinforcement and meshes; it withstands heavy incidental weights and loads with great stability.

MULTIPIEDE

GREY HD POLYETHYLENE

GREY HD POLYPROPYLENE

bar length 50 cm - Pack. 100 Pcs (DMP 30 - Pack 75 Pcs)

| - | | | | |
|---------|------|------|---------|---|
| Article | H mm | €/Pc | €/Pack. | |
| DMP 20 | 20 | | | * |
| DMP 25 | 25 | | | * |
| DMP 30 | 30 | | | * |

Maximum weight:

2.500 kg a piece (bar lenght: 50 cm) equally distributed.

