

PROFOIL

ROLLS IN HDPE AND PP

PROFOIL is a waterproofing polyethylene membrane with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.



ROLLS IN HDPE AND PP - Thickness 0,42 mm

Article	Width roll H x L lm	total m ²			
PFLO 0430	1 x 30	30	40		
PFLO 0405	1 x 5	5	154		

AREAS OF USE

- **Use.** Waterproofing of substrates and vertical structures before the laying of ceramic and stone materials in areas subject to occasional contact with water like bathrooms and kitchens, with high vapor pressure like saunas and Turkish baths and with permanent contact with water also in pressure like swimming pools and tanks. On screed without cracks and completely cured, old ceramic floors and natural stones anchored to the substrate, concrete completely cured and wood supports.
- **Don't use.** On bituminous coverings, over insulating panels and lightweigh screed.

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat. Read the data sheet before applying; in case of special applications please call the technical department.

PROFOIL PASTE

WATERPROOFING ELASTIC MEMBRANE

PROFOIL PASTE is a ready to use thin-layer waterproofing elastic membrane with low emissions of volatile organic compounds.



WATERPROOFING ELASTIC MEMBRANE

Article	Kg./Bucket	Bucket/ Pallet			
PFLOPST 04	4	64			
PFLOPST 10	10	36			

AREAS OF USE

- **Use.** Waterproofing for bathrooms, kitchens, showers, gypsum-based plasters, cement-based plaster and plaster-board walls.
- **Don't use.** For external application, on wet surfaces or substrates subject to moisture rising, in environments where water is always present, pools and tanks.

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat. Read the data sheet before applying; in case of special applications please call the technical department.

PROBAND 150/250

ROLLS IN HDPE AND PP

PROBAND 150/250 is a waterproofing polyethylene tape with nonwoven polypropylene fabric on both side that guarantees high adhesion to the support.




ROLLS IN HDPE AND PP - Thickness 0,42 mm

Article	Roll width H mm x L lm	Rolls/ Pack.			
PRBPE 1505	150 x 5	20			
PRBPE 1507	150 x 7,5	16			
PRBPE 1530	150 x 30	6			
PRBPE 2505	250 x 5	10			
PRBPE 2530	250 x 30	3			


PRBPE 1505 available while stocks last

AREAS OF USE AND WARNINGS, see page 179

PREFORMED CORNERS and PIPE COLLAR



EXTERNAL CORNER



INTERNAL CORNER



PIPE COLLAR

PREFORMED CORNERS AND PIPE COLLAR IN HDPE AND PP

Thickness 0,42 mm

Article	H x L mm	Rolls/Pack.			
PRBI (internal)	150 x 150	10 Pcs			
PRBE (external)	150 x 150	10 Pcs			
PRBT (pipe collar)	125 x 125	10 Pcs			

Internal and external preformed corners and pipe collar in polyethylene provided on both side with nonwoven polypropylene fabric that guarantees its adhesion to the support.

AREAS OF USE AND WARNINGS, see page 180

PRODRAIN 10

MEMBRANA DRENANTE

PRODRAIN 10 is a drainage membrane composed by an high density polyethylene (HDPE) sheet provided with truncated cone reliefs. On the top of the reliefs a non-woven polypropylene fabric, in grey colour, permeable to water is thermowelded.



DRAINAGE MEMBRANE

Thickness H 10 mm - Total 12,0 m² - 6 ROLLS PER PALLET = 72 m²

Article	H roll (MT)	L roll (MT)	roll x pallet		
PDRI 10	0,96	12,5	6		

AREAS OF USE

- **Use.** Outside on concrete sloping suitably waterproofed such as terraces, balconies and pavements and in contact with waterproofed vertical structures such as foundation walls. Highly resistant to saline solutions, acid and alkaline, alcohol and oils. In case of special products consult the technical department.
- **Don't use.** On concrete waterproofed without adequate slope to the drained water runoff. As soundproof and thermal-insulating layer.

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat. Read the data sheet before applying; in case of special applications call the technical department.