

PROEND INS 75 is a step nosing profile in anodized aluminium with interchangeable rubber insert: the upper part is knurled to increase slip and slide resistance and is applied after laying. Available anodized with gold,

bronze or silver finish and with adhesive or punched. **PROEND INS 75** ensures a perfect finish, covering laying defects and protecting the edge. Easy to lay with the self-adhesive backing ensuring perfect adherence to the step or with screws and screw anchors in the punched version.

PROEND INS 75

GOLD, SILVER AND BRONZE ANOD. ALUMINIUM ADHESIVE AND PUNCHED

L 75,5 mm

PED... 7537A/F scale 1:1



ANODIZED ALUMINIUM with DOUBLE INSERT thermo packed - with adhesive

| Dar length 2,7 m - pack. 10 PCS - 27 m | | | | |
|--|-----------|------|------|--|
| Article | H x L mm | €/lm | €/Pc | |
| PED 7537A | 37 X 75,5 | | | |
| | | | | |

ANODIZED ALUMINIUM with DOUBLE INSERT

thermo packed - punched

bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article H x L mm

PED... 7537F 37 X 75,5

On demand bar length 3 Im with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed.

€/lm

€/Pc

Available in the finishes: AA - AO - AB. The code of the selected finish must be added to the article code. E.g.:PED... 7537A (chosen finish anodized gold) PEDAO 7537A.

silver finish and with adhesive or punched.




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS Adhesive version

1. Choose the suitable profile and cut it to the necessary length 2. Degrease, wash and clean the solid surface throughly. **3.** Remove the protective paper from the adhesive. **4.** Lay the profile by applying pressure evenly over the whole surface without using a hammer **Punched version**

 Choose the suitable profile and cut it to the necessary length.
Mark the position of the holes using the existing holes in the profile as reference.
Insert the screw anchors into the drilled holes.
Fix the profile using flathead screws suitable for the relative slots in the profile.


COLOURS






PROEND INS

PROEND INS is a step nosing profile in anodized aluminium with interchangeable rubber insert: the upper part is knurled to increase slip and slide resistance and is applied after laying. Available anodized with gold, bronze or **PROEND INS** ensures a perfect finish, covering laying defects and protecting the edge. Easy to lay with the self-adhesive backing ensuring perfect adherence to the step or with screws and screw anchors in the punched GOLD, SILVER AND BRONZE ANOD. ALUMINIUM



EXAMPLES OF LAYING



For instructions see the product above

ANODIZED ALUM. with adhesive WITH INSERT thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm Article HxLmm €/Im €/Pc


| | 1 |
|--|---|
| | |
| | |


ANODIZED ALUM. punched WITH INSERT thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

| Article | H x L mm | €/lm | €/Pc |
|-----------|----------|------|------|
| PED 4528F | 28 X 45 | | |

AA - Anodized silver alum. AO - Anodized gold alum. AB - Anodized bronze alum.

On demand bar length 3 Im with minimum quantity of 200 pcs. Production delay 4/5 weeks. Price to be agreed.







28 X 45

The code of the selected colour must be added to the article code E.g.: PED... 4528A (chosen finish anodized gold) PEDAO 4528A


BLACK INTERCHANGEABLE INSERT


COLOURS

VINYL RESIN / RUBBER

IIN 12

VINYL RESIN / RUBBER bar length 2,7 lm - pack. 20 Pcs - 54 lm Article €/lm





version

PED... 4528A

© 2022 All rights reserved by Progress Profiles. Printed in Itely

🚼 = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed Prices are referred to whole packs, 10% increase for minimum orders of 10 pcs, 20% increase for orders of less than 10 pcs.

€/Pc

stair

nosing for existing steps

H:37 n