



PROEND 5050



DESCRIPTION

PROEND 5050 is a profile in aluminium with a non-slip insert in carborundum for stairs. Its particular section and the availability of the carborundum in six colour, make it an elegant and valued profile also in case of modern stairs.

MATERIAL

PROEND 5050 is a profile in anodized silver aluminium with a non-slip insert in carborundum for stairs. The profile has a horizontal visible surface, partially knurled, of 50 mm on which the non-slip insert in carborundum will be fixed. The vertical side, with a grade of 83° and a visible surface of 50 mm, is perfectly smooth. It is available with adhesive and punched. The punched version can be fix with screws. Its particular section and the availability of the carborundum in six colour, make **PROEND 5050** an elegant and valued profile also in case of modern stairs.

AREAS OF USE

PROEND 5050 in anodized aluminium is suitable for indoors environment where good resistance to mechanical and chemical stresses are required.

WARNINGS

Don't use **PROEND 5050** in anodized aluminium outdoors and in environments where aggressive substances are used. Clean immediately the surface of the profile from all remains of alkaline

substances; the permanence of these substances on the surface may lead to formation of non-removable aluminium hydroxide (dark halos).

MAINTENANCE

PROEND 5050 does not require any special maintenance; it is recommended to clean it with normal household cleaning products.

LAYING INSTRUCTIONS



1. Choose "**PROEND 5050**" according to the desired fixing.
2. Cut "**PROEND 5050**" to the desired length.

With adhesive

3. Remove all remains of oil, grease and dirt from the surface where the profile will be laid.
4. When the surface is dry, remove the protective film.
5. Correctly position the profile and press it without hitting.
6. Apply the carborundum strip in the desired colour.

Punched version

3. Align the profile and mark the position of the holes on the support.
4. Drill the support with a 5 mm diameter bit and insert the 5 x 25 mm rawlplugs.
5. Align the profile to the holes and screw it.
6. Apply the carborundum strip in the desired colour.



TEXT TEMPLATE FOR TENDERS

Delivery and installation of profile in anodized silver aluminium with a non-slip insert in carborundum for stairs. The profile with adhesive / punched has a horizontal visible surface, partially knurled, of 50 mm on which the non-slip insert in carborundum will be fixed. The vertical side, with a grade of 83° and a visible surface of 50 mm, is perfectly smooth, like PROEND 5050 of the Progress Profiles company.

PEGRAA 50A / F: Anodised silver aluminium.

Profile width : _____ mm
Profile length : _____ mt
Material : _____ €/mt
Application : _____ €/mt
Total value : _____ €/mt