



PRODRIP is a perimeter drain in ASA (Modified ABS) equipped with wall-floor junction. The junction is covered with non-woven polypropylene to ensure sealing with the used waterproofing system.

PRODRIP

PERIMETER DRAIN

PERIMETER DRAIN

pack. per pallet = 192

| Article | Colour | Pcs/Pack. | | |
|---------|--------|-----------|--|--|
| PDRP | Grey | 4 | | |

AREA OF USE

• Use

To realise perimeter drains on balconies, terraces and outside horizontal surfaces of any size.


• Don't use

With bituminous waterproofing and as vertical drain.

WARNINGS

Do not heat with direct flames and do not use adhesive with solvents.

Consult the data sheet prior to application in the case of special applications, we recommend that you consult the technical department.



PROBAND KOLL is a single-component hydrophobic adhesive for the sealing of PROBAND 150/250 on PRODES® MEMBRANE and PRODES® HEAT/GRIP MEMBRANE.

PROBAND KOLL

SINGLE-COMPONENT HYDROPHOBIC ADHESIVE

FAST SETTING SINGLE-COMPONENT HYDROPHOBIC ADHESIVE

Bucket of 20 Kg. Bucket per pallet = 30 Pcs per pallet 600 Kg.

| Article | Colours | Bucket Kg. | | |
|---------|---------|------------|--|--|
| PRBK | RED | 20 | | |

AREA OF USE

• Use

For the sealing of the tape PROBAND 150/250 with PRODES® MEMBRANE and PRODES® HEAT/GRIP MEMBRANE on balconies, terraces, bathrooms, kitchens, saunas and external surfaces of any size.

• Don't use

On bituminous coverings, to glue tiles and to waterproof cement based support.

Do not use outside with PRODES® HEAT/GRIP MEMBRANE

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat.

Read the data sheet before applying; in case of special applications call the technical department.



PROBAND BU is an adhesive tape in butyle provided on one side with non-woven polypropylene that guarantees high adhesion.

PROBAND BU

BUTYLE TAPE

BUTYLE TAPE - Thickness 1 mm

| Article | H roll (mm) | L roll (lm) | Roll / | | |
|------------|-------------|-------------|--------|--|--|
| PRBBU 7515 | 75 | 15 | 2 | | |

AREA OF USE

• Use

Realization of perimeter junctions in case of bituminous coverings, PVC, wood, polycarbonate, glass, plastic and metal on balconies, terraces and external surfaces of any size.

• Don't use

On dirty, incoherent and wet surfaces.

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat.

Read the data sheet before applying; in case of special applications call the technical department.



PROBAND FIX is a moisture-cure sealant with high adhesion and elasticity. It guarantees the adhesion of PROBAND 150/250 with aluminium frames, plastic and metal and between adjacent sheets of PROFOIL.

PROBAND FIX

MOISTURE-CURE SEALANT

MOISTURE-CURE SEALANT

pack. of 12 cartridges

| Article | Colours | Cartridge lm | | |
|---------|---------|--------------|--|--|
| PRBFXB | WHITE | 290 | | |
| PRBFXG | GREY | 290 | | |

COLORS

| | |
|-----------|----------|
| | |
| B - White | G - Grey |

AREA OF USE

• Use

For the fastening of PROBAND 150/250 on supports in PVC, polycarbonate, plastic and metal. For sealing Proband 150/250 between adjacent sheets of PROFOIL in tanks and pools.

• Don't use

On bitumen membranes. To seal PROBAND with PRODES®.

For more details see page 256.

WARNINGS

Store in a cool and dry place avoiding direct sunlight and sources of heat.

Read the data sheet before applying; in case of special applications call the technical department.

