


PROSOL 30-35-40


PUNCHED STAINLESS STEEL 1.4016
WITH PROTECTIVE FILM

PROSOL 30-35-40 in steel are punched joint - covers in stainless steel 1.4016 available in various widths. They are used to join floors of the same or differing material and thickness. The rounded shape also allows the profile to be used to edge shallow floors max. 5 mm thick. **PROSOL** is normally used to cover flaws and defects created during laying of ceramic/wood/parquet floors by covering the joint/threshold. **PROSOL** is recommended for all sorts of public environments: hotels, offices, shops and private dwellings; it guarantees an impeccable and attractive finish.


PLSAC 30F/308F/309F/308FS/309FS/3010FS/3016FS





PLSAC 35F/358F/359F/358FS/359FS/3516FS



PLSAC 40F/409FS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Mark the position of the holes using the existing holes in the profile as reference.
3. Insert the screw anchors into the drilled holes.
4. Fix the profile using flathead screws suitable for the relative slots in the profile.



STAINLESS ST. 1.4016 punched - with protective film
bar length 2,7 lm - pack. 20 Pcs - 54 lm (L 30 mm - 108 lm)

Article	Width-thick.		
PLSAC 30F	30 mm - 10/10		
PLSAC 35F	35 mm - 10/10		
PLSAC 40F	40 mm - 12/10		

STAINLESS ST. 1.4016 punched thermo packed
bar length 0,83 lm - pack. 20 Pcs

Article	Width-thick.		
PLSAC 308F	30 mm - 10/10		
PLSAC 358F	35 mm - 10/10		*

STAINLESS ST. 1.4016 punched thermo packed
bar length 0,93 lm - pack. 20 Pcs

Article	Width-thick.		
PLSAC 309F	30 mm - 10/10		
PLSAC 359F	35 mm - 10/10		*

COLOURS



AC - Polished stainless
Steel 1.4016

On demand hand-brushed stainless steel (Prices to be agreed. Production delay 4/5 weeks)

STAINLESS ST. 1.4016 punched with screws and screw anchors
thermo packed - bar length 0,83 lm - pack. 20 Pcs

Article	Width-thick.		
PLSAC 308FS	30 mm - 10/10		
PLSAC 358FS	35 mm - 10/10		*

STAINLESS ST. 1.4016 punched with screws and screw anchors
thermo packed - bar length 0,93 lm - pack. 20 Pcs

Article	Width-thick.		
PLSAC 309FS	30 mm - 10/10		
PLSAC 359FS	35 mm - 10/10		*
PLSAC 409FS	40 mm - 12/10		*

STAINLESS ST. 1.4016 punched with screws and screw anchors
thermo packed - bar length 1,03 lm - pack. 20 Pcs

Article	Width-thick.		
PLSAC 3010FS	30 mm - 10/10		

STAINLESS ST. 1.4016 punched with screws and screw anchors
thermo packed - bar length 1,66 lm - pack. 20 Pcs

Article	Width-thick.		
PLSAC 3016FS	30 mm - 10/10		
PLSAC 3516FS	35 mm - 10/10		*

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed