



**PROFLOOR 712** is a self-adhesive sloping terminal transition profile in AISI 304/1.4301-V2A stainless steel with protective film. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble. It joins and compensates a thickness between 7 and 12mm. **PROFLOOR 712** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.

## PROFLOOR 712

POLISHED STAINLESS STEEL  
AISI 304/1.4301-V2A WITH SELF-ADHESIVE



POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs

Article	L x H mm		
PFRAC 7129AS	38 X 7/12		

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 1,66 lm - pack. 20 Pcs

Article	L x H mm		
PFRAC 71216AS	38 X 7/12		

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm		
PFRAC 71212A	38 X 7/12		

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 0,83 lm - pack. 20 Pcs

Article	L x H mm		
PFRAC 7128AS	38 X 7/12		

POLISHED STAINLESS ST. AISI 304/1.4301-V2A self-adhesive thermo packed - bar length 1,03 lm - pack. 20 Pcs

Article	L x H mm		
PFRAC 71210AS	38 X 7/12		

### COLOURS




On demand hand-brushed stainless steel (Prices and delivery time to be agreed)


AC - Polished stainless steel AISI 304/1.4301-V2A

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

PFRAC 712A/7128AS/7129AS/71210AS/71216AS



### EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

transition profiles

**PROFLOOR 712** is a self-adhesive sloping terminal transition profile in polished brass with protective film. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble. It joins and compensates a thickness between 7 and 12mm. **PROFLOOR 712** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.

## PROFLOOR 712

POLISHED BRASS  
WITH SELF-ADHESIVE



POLISHED BRASS self-adhesive thermo packed bar length 0,93 lm - pack. 20 Pcs

Article	L x H mm		
PFROL 7129AS	38 X 7/12		

POLISHED BRASS self-adhesive thermo packed bar length 1,66 lm - pack. 20 Pcs

Article	L x H mm		
PFROL 71216AS	38 X 7/12		

POLISHED BRASS self-adhesive thermo packed bar length 2,7 lm - pack. 20 Pcs - 54 lm

Article	L x H mm		
PFROL 7121A	38 X 7/12		


POLISHED BRASS self-adhesive thermo packed bar length 0,83 lm - pack. 20 Pcs

Article	L x H mm		
PFROL 7128AS	38 X 7/12		

POLISHED BRASS self-adhesive thermo packed bar length 1,03 lm - pack. 20 Pcs


Article	L x H mm		
PFROL 71210AS	38 X 7/12		

### COLOURS




OL - Polished brass

PFROL 712A/7128AS/7129AS/71210AS/71216AS



### EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the suitable profile and cut it to the necessary length.
2. Degrease, wash and clean the solid surface thoroughly.
3. Remove the protective paper from the adhesive.
4. Lay the profile by applying pressure evenly over the whole surface without using a hammer.

transition profiles

**PROFLOOR 712** is a self-adhesive sloping terminal transition profile in anodised aluminium with silver-gold-bronze finish with protective film. It is used to give a clean-cut, elegant finish when joining and compensating differences in level of floors that are already laid and in differing or same materials e.g. ceramic tiles-wood-parquet-marble. It joins and compensates a thickness between 7 and 12mm. **PROFLOOR 712** ensures a perfect finish with little height, covering any flaws created during laying of the floor. Easy to lay; the high-strength elastomer adhesive ensures an excellent grip.

## PROFLOOR 712

ANODISED GOLD, SILVER AND BRONZE  
ALUMINIUM WITH SELF-ADHESIVE



ANODISED ALUMINIUM self-adhesive thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm


Article	L x H mm		
PFR... 7121A	38 X 7/12		



ANODISED ALUMINIUM self-adhesive thermo packed - bar length 0,93 lm - pack. 20 Pcs

Article	L x H mm		
PFR... 7129AS	38 X 7/12		

PFR... 712A/7129AS



### COLOURS



AA - Anodised silver alum. AO - Anodised gold alum. AB - Anodised Bronze Alum.  
Available on demand anod. titanium, champagne and sand alum. with a minimum quantity order of 270 lm

transition profiles

Available in the colours: AA - AO - AB (AT, CH and SB available on demand with a minimum quantity order of 270 lm). The code of the selected colour must be added to the article code. E.g. PFR... 7121A (chosen colour anodised gold alum.) PFRAC 7121A.