



PROELEGANT


NATURAL, POLISHED AND CHROMED
BRASS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the "PROELEGANT" with the same height as the thickness of the wall covering/floor. 2. Apply the adhesive onto the area of application of the profile. 3. Lay and align the profile pressing the perforated flange into the adhesive. 4. Lay the tiles, aligning them so that the top edge of the profile is "flush" with the tile. 5. Use the adhesive to seal any empty interstices. Oxidation marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidol, Smac and similar.



POLISHED BRASS thermo packed

bar length 2,7 lm - pack 20 Pcs - 54 lm

Article	H mm		
PELOL 08	8		*
PELOL 10	10		
PELOL 125	12,5		
PELOL 14	14		*

NATURAL BRASS thermo packed 10 Pcs

bar length 2,7 lm - pack 20 Pcs - 54 lm

Article	H mm		
PELON 08	8		*
PELON 10	10		
PELON 125	12,5		
PELON 14	14		*

COLOURS

OC - Chromed brass	OL - Polished brass	ON - Natural brass



CHROMED BRASS thermo packed

bar length 2,7 lm - pack 20 Pcs - 54 lm

Article	H mm		
PELOC 08	8		*
PELOC 10	10		
PELOC 125	12,5		
PELOC 14	14		*

NATURAL BRASS thermo packed 5 Pcs



bar length 0,90 lm - pack 40 Pcs - 36 lm

Article	H mm		
PELON 089	8		*
PELON 109	10		*
PELON 1259	12,5		*

PROELEGANT

NATURAL ALUMINIUM AND
ANODISED SILVER ALUMINIUM

EXAMPLES OF LAYING (for instructions see the product over)



Curve available, see page 174



NATURAL ALUMINIUM thermo packed 10 Pcs

bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	H mm		
PELAN 08	8		*
PELAN 10	10		
PELAN 125	12,5		

COLOURS

AN - Natural alum.	AA - Anodised silver alum.



ANODISED SILVER ALUMINIUM thermo packed

bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	H mm		
PELAA 08	8		*
PELAA 10	10		
PELAA 125	12,5		

* = On demand, price and delivery time to be agreed.