

PROINTER AL

ANODIZED AND POLISHED ALUMINIUM

PROINTER AL is a cove-shaped profile in anodized and polished aluminium. It is particularly suitable to ensure cleanliness and hygiene is suitable in indoors environment where good resistance to mechanical and chemical stresses are required. Its particular section and the availability in four finishes and special pieces, such as internal and external corners, make **PROINTER AL** a much sought after profile. The profile is easy to match with the wall covering and allows a workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROINTER AL" according to the tile thickness and desired finish.
2. Cut "PROINTER AL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of the support where the profile will be laid. **3.** Press the ancioning liange of "PROINTER AI," into the adhesive. **4.** Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. **5.** Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



ANODIZED GOLD OR SILVER ALUMINIUM thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm	€/lm	€/Pc	
PIAA 08	8			
PIAA 10	10			
PIAO 08	8			+
PIAO 10	10			4

INTERNAL, EXTERNAL, THREE-WAYS PROINTER CORNER JOINTS ANODIZED GOLD (AO) or SILVER ALUMINIUM (AA) - pack. 2 Pcs

Article	€/Pack. 2 Pcs
REPI/2	
RIPI/2	
RITPI/2	

Corners of the on demand profiles are also on demand 🚼






POLISHED GOLD OR CHROMED ALUMINIUM thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm	€/lm	€/Pc	
PIBC 08	8	,		_
PIBC 10	10			
PIBO 08	8			*
PIBO 10	10			×

INTERNAL, EXTERNAL, THREE-WAYS PROINTER CORNER JOINTS

POLISHED GO	LD (BO) or CHROME	D A	KLUMINIUM (BC) - pack. 2 PCS
	Article		€/Pack. 2 Pcs
REPI/2			
RIPI/2			
RITPI/2			
RITPI		RIF	PI
EXTERNAL CORNER			NTERNAL CORNER






PROINTER KL ALL

POLISHED AND CHROMED BRASS AND ANODIZED AND POLISHED ALUMINIUM

PROSHELL KL ALL is a cove-shaped profile in polished and chromed brass and anodized and polished aluminium. The profile allows to connect the floor and wall coverings in ceramic and mosaic also with low thickness. It is particularly suitable to ensure cleanliness and hygiene in every kind of environment where good resistance to mechanical and chemical stresses are required. Its particular section and availability in five different finishes, make PROSHELL KL ALL a much sought after profile.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROINTER KL ALL" according to the desired finish. 2. Cut "PROINTER KL ALL" to the desired length. 3. Apply the silicone along the floor-wall connection. 4. Press the arrowhead of "PROINTER KL". ALL" into the silicone evenly until t is completely adherent to the

Corners of the on demand profiles are also on demand 🚼



POLISHED / CHROMED BRASS thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm	€/lm	€/Pc	
PIKLOL 045	4,5			
PIKLOC 045	4,5			7

CAPS - VARNISHED PLASTIC

	Article	€/Pack. 2 Pcs	€/Pack. 10 Pcs
- 1	TDIKI /		









POLISHED CHROME ALUMINIUM / GOLD thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm	€/lm	€/Pc
PIKLBC 045	4,5		
PIKLBO 045	4,5		

ANODIZED SILVER ALUMINIUM thermo packed bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm	€/lm	€/Pc
PIKLAA 045	4,5		

CAPS - VARNISHED PLASTIC

Article	€/Pack. 2 Pcs	€/Pack. 10 Pcs
TPTPIKL/		
COLOURS		
AA - Anodized silver alum.	BC - Polished chrome alum.	BO - Polished gold alum.

* = Production on demand with minimum quantity of 100 pcs. Production delay 4/5 weeks. Price to be agreed

