PROLISTEL ALL is a listel in anodized, polished and brushed aluminium with a rounded visible surface, suitable to decorate the wall coverings in ceramic, mosaic and natural stone. Its particular section and availability in different finishes, make **PROLISTEL P ALL** a much sought after profile. It can be used with the range of PROJOLLY profiles to decorate the wall coverings and to allow an elegant workmanlike application.

PROLISTEL ALL

ANODIZED, POLISHED AND BRUSHED ALUMINIUM



POLISHED ALUMINIUM (chrome-gold-copper-titanium-black) thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm


	,			
Article	H mm	€/lm	€/Pc	
PLTBC 15	15			
PLTBR 15	15			*
PLTBT 15	15			
PLTBO 15	15			*
PLTBN 15	15			*
PLTBC 25	25			
PLTBR 25	25			*
PLTBT 25	25			
PLTBO 25	25			*
PLTBN 25	25			*

ANODIZED ALUMINIUM (silver-gold-copper-titanium-black) thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm	€/lm	€/Pc
PLTAA 15	15		
PLTAR 15	15		
PLTAT 15	15		
PLTAO 15	15		
PLTNE 15	15		
PLTAA 25	25		
PLTAR 25	25		
PLTAT 25	25		
PLTAO 25	25		
PLTNE 25	25		

BRUSHED POLISHED ALUMINIUM (silver-gold-copper-titanium-black) **thermo packed** - bar length **2,7 lm** - pack. **40 Pcs - 108 lm**

Article	H mm	€/lm	€/Pc	
PLTBS 15	15			
PLTRS 15	15			*
PLTTS 15	15			
PLTBOS 15	15			*
PLTNS 15	15			*
PLTBS 25	25			
PLTRS 25	25			*
PLTTS 25	25			
PLTBOS 25	25			* *
PLTNS 25	25			*



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROLISTEL ALL" according to the width and desired finish. 2. Cut "PROLISTEL ALL" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press "PROLISTEL ALL" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS

ANODIZED POLISHED		BRUSHED POLISHED		
AA - Anodized silver alum. AT - Anodized titanium alum.	NE - Anodized black alum.	BC - Polished chrome alum.	BT - Polished titanium alum.	BS - Brushed polished silver alum. TS - Brushed Polished titanium alum.

AVAILABLE MINIMUM QUANTITY 100 PCS by colour and height (Price to be agreed. Production delay 4/5 weeks)

ANODIZED			POLISHED BRUSHED POLISHED			RUSHED POLISHED
AO - Anodized Gold alum	AR - Anodized conner alum	RO - Polished Gold alum	RR - Polished conner alum	RN - Polished black alum	ROS - Brushed Gold alum	RS - Brushed Polished conner alum NS - Brushed Polished h

On demand may be realised in other finishes of the colour chart. Contact our customer service for minimal quantity, timing and price.

PROLISTEL LED is a listel in anodized and polished aluminium equipped with an integrated LED lighting system that can generate a cold, hot and neutral suffused light. It is suitable to decorate the wall coverings in ceramic, mosaic and natural stone. Its particular section and availability in different finishes, make **PROLISTEL LED** a much sought after profile that decorates the wall coverings.

PROLISTEL LED

ANODIZED AND POLISHED ALUMINIUM



ANODIZED ALUM. SILVER, POLISHED CHROME ALUMINIUM thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm ADAPTOR LED, LED & FLAT NOT INCLUDED

Article	H mm	€/lm	€/Pc
PLTLEDAA 20	20		
PLTLEDBC 20	20		

ADHESIVE FLEXIBLE LED COIL

length 5 lm - pack. 1 ROLL

Article	€/lm	€/Pack
LEDN		
LEDF		
LEDC		

COLOURS

AA - Anodized silver alum.	BC - Polished chrome alum.





PIAO 17

FND CAPS - R/I (3 right & 3 left)


LIND CAL 3 - IO L (3 LIBILL)	x J ICIL)		
Article	H mm	€/Pack	1
TPLTLEDAA 20	20		
TPLTLEDBC 20	20		q
LED ADAPTOR AC/DC 7	5W - 12V (15 lm)		

LED ADAPTOR AC/DC 75W - 12V (15 IM)


ALL 7512 LED ADAPTOR AC/DC 25W - 12V (5 lm)

Article €/Pc

ALL 2512



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROLISTEL LED" according to the width and desired finish. 2. Cut "PROLISTEL LED" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press "PROLISTEL LED" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

