



PROBORD is a round corner bead profile in polished and satin finish stainless steel AISI 304/1.4301-V2A suitable to protect the external corner of wall coverings in ceramic. Its particular section and availability in two different finishes, make **PROBORD** a much sought after profile. It can be used with the range of PROLISTEL and PROSHELL profiles to obtain an elegant workmanlike application even in environments subject to high mechanical stresses.

PROBORD

POLISHED AND SATIN FINISH STAINLESS
STEEL AISI 304/1.4301-V2A



POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm - 10/10mm

Article	H mm		
PEBDAC 08	08		
PEBDAC 10	10		
PEBDAC 125	12,5		



SATIN STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm - 10/10mm

Article	H mm		
PEBDACS 08	08		
PEBDACS 10	10		
PEBDACS 125	12,5		

COLOURS




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS




SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

1. Choose "PROBORD" according to the tile thickness and desired finish.
2. Cut "PROBORD" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROBORD" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.


PEBDAC/ACS 08



PEBDAC/ACS 10



PEBDAC/ACS 125



PROEDGE FLEX

SHOCKPROOF NON - TOXIC CO-EXTRUDED
COLORED VINYL RESIN




CO-EXTRUDED PVC - L 40 X 40 mm
bar length 2,7 lm - pack. 15 Pcs - 40,5 lm

Article	H mm		
PFC01 40 (without adhesive)	40		
PFC01 40A (with adhesive)	40		




COLOURS



AVAILABLE MINIMUM QUANTITY 270 LM
by colour and height (price and delivery time to be agreed)

PFC... 40/40A
scale 1:2



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROEDGE FLEX" according to the desired colour.
2. Cut "PROEDGE FLEX" to the desired length.
3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid.
4. When the surface is perfectly dry, remove the protective film (version with adhesive), place correctly the profile and press it without hitting / apply the silicone on the surface where the profile will be laid (version without adhesive) and press it without hitting.