

PROEDGE AC


POLISHED AND SATIN FINISH
STAINLESS STEEL AISI 304/1.4301-V2A

PROEDGE AC is a corner bead profile in polished and satin finish stainless steel AISI 304/1.4301-V2A suitably shaped to protect the external corner of wall coverings. Its particular section, the availability in two different finishes and seven widths make **PROEDGE AC** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.


PEG... 50A



PEG... 40A



PEG... 30A




PEG... 25A



PEG... 20A



PEG... 15A



PEG... 10A



POLISHED AND SATINED STAINLESS STEEL WITH ADHESIVE with protective film - bar length 2,7 lm - pack. 81 lm - 8/10 mm

Article	LxH mm		
PEGAC 10A (polished stainless steel)	10 x 10		
PEGAC10A (satin finish stainless steel)	10 x 10		
PEGAC 15A (polished stainless steel)	15 x 15		
PEGAC15A (satin finish stainless steel)	15 x 15		
PEGAC 20A (polished stainless steel)	20 x 20		
PEGAC20A (satin finish stainless steel)	20 x 20		

POLISHED AND SATINED STAINLESS STEEL WITH ADHESIVE with protective film - bar length 2,7 lm - pack. 27 lm - 12/10 mm

Article	LxH mm		
PEGAC 40A (polished stainless steel)	40 x 40		
PEGAC40A (satin finish stainless steel)	40 x 40		
PEGAC 50A (polished stainless steel)	50 x 50		
PEGAC50A (satin finish stainless steel)	50 x 50		

For items without adhesive, write the item without the final A. E.g.: PEGAC. 40.

COLOURS



1. Choose "PROEDGE AC" according to the desired finish and width.
2. Cut "PROEDGE AC" to the desired length. 3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid. 4. When the surface is perfectly dry, remove the protective film, place correctly the profile and press it without hitting / apply the silicone on the surface where the profile will be laid (version without adhesive) and press it without hitting.

Suitable for use in contact with foodstuffs.

PROEDGE OT

POLISHED AND CHROMED BRASS

PROEDGE OT is a corner bead profile in polished and chromed brass suitably shaped to protect the external corner of wall coverings. Its particular section, the availability in two different finishes and seven widths make **PROEDGE OT** a much sought-after profile that allows an elegant workmanlike application.

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROEDGE OT" according to the desired finish and width.
2. Cut "PROEDGE OT" to the desired length. 3. Remove carefully any remains of oil, fat and dirt from the surface where the profile will be laid. 4. When the surface is perfectly dry, remove the protective film, place correctly the profile and press it without hitting / apply the silicone on the surface where the profile will be laid (version without adhesive) and press it without hitting.

COLOURS



CHROMED BRASS WITH ADHESIVE
thermo packed - bar length 2,7 lm - pack. 54 lm

Article	LxH mm		
PEGOC 10A	10 x 10		
PEGOC 15A	15 x 15		
PEGOC 20A	20 x 20		
PEGOC 25A	25 x 25		
PEGOC 30A	30 x 30		

MIRROR LINE

POLISHED BRASS WITH ADHESIVE
bar length 2,7 lm - pack. 27 lm - 10/10 mm

Article	LxH mm		
PEGOL 25A	25 x 25		*
PEGOL 30A	30 x 30		*

MIRROR LINE

POLISHED BRASS WITH ADHESIVE
bar length 2,7 lm - pack. 54 lm - 8/10 mm

Article	LxH mm		
PEGOL 10A	10 x 10		
PEGOL 15A	15 x 15		*
PEGOL 20A	20 x 20		*

MIRROR LINE

POLISHED BRASS WITH ADHESIVE
bar length 2,7 lm - pack. 27 lm - 12/10 mm

Article	LxH mm		
PEGOL 40A	40 x 40		*
PEGOL 50A	50 x 50		*

MIRROR LINE

For items without adhesive, write the item without the final A. E.g.: PEGOL. 10.

For items without adhesive, write the item without the final A. E.g.: PEGOL. 25.

= On demand, price and delivery time to be agreed.