

PROJOLLY QUART is a quarter-circle rounded bead profile in polished, super polished and satin finish stainless steel AISI 304/1.4301-V2A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section, the availability in three different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY QUART** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.



COLOURS



PROJOLLY QUART

POLISHED, SUPER POLISHED AND SATIN FINISH STAINLESS STEEL AISI 304/1.4301-V2A

POLISHED STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack 30 Pcs - 10/10mm

Article	H mm
PJQTAC 045 (81 LM)	4,5
PJQTAC 06 (54 LM)	6

SUPER POLISHED STAINLESS STEEL AISI 304/1.4301-V2A thermo packed
bar length 2,7 lm - pack 30 Pcs

Article	H mm
PJQTACML 045	4,5
PJQTACML 06	6

SATIN STAINLESS STEEL AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack 30 Pcs - 81 lm - 10/10mm

Article	H mm
PJQTACS 045	4,5
PJQTACS 06	6

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY QUART" according to the tile thickness and desired finish. 2. Cut "PROJOLLY QUART" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY QUART" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

profiles for low thicknesses

CAPSULES, END CAPS and THREE-WAYS JOINTS

POLISHED, SUPER POLISHED AND SATIN STAINLESS STEEL AISI 304/1.4301-V2A / PLASTIC

CAPSULES and END CAPS - POLISHED STAINLESS STEEL
AISI 304/1.4301-V2A

Article	H mm
CPJQTAC 045/... (external)	4,5
IPJQTAC 045/... (internal)	4,5
TPJQTAC 045/... (end cap)	4,5

Choose the desired packaging. E.g.: CPJQTAC .../10 (Pack. 10 Pcs)
CPJQTAC .../2 (Pack. 2 Pcs)

CAPSULES and END CAPS - SATIN STAINLESS ST. AISI 304/1.4301-V2A

Article	H mm
CPJQTACS 045/... (external)	4,5
IPJQTACS 045/... (internal)	4,5
TPJQTACS 045/... (end cap)	4,5

Choose the desired packaging. E.g.: CPJQTACS .../10 (Pack. 10 Pcs)
CPJQTACS .../2 (Pack. 2 Pcs)

CAPSULES SUPER POLISHED STAINLESS STEEL
AISI 304/1.4301-V2A


Article	H mm
CPJQTACML 045/... (external)	4,5
IPJQTACML 045/... (internal)	4,5

Choose the desired packaging. E.g.: CPJQTACML .../10 (Pack. 10 Pcs)
CPJQTACML .../2 (Pack. 2 Pcs)

JOINTS - PLASTIC

Article	H mm
GIJQT 045/...	4,5

Choose the desired packaging. E.g.: GIJQT .../10 (Pack. 10 Pcs)
GIJQT .../2 (Pack. 2 Pcs)



PROJOLLY is a rounded bead profile in anodized aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings and like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles. Its particular section and elegance, the availability in seven different finishes and special pieces such as internal and external corners, end caps and joints make **PROJOLLY** a much sought-after and elegant profile that allows a workmanlike application.


PROJOLLY

ANODIZED, POLISHED AND BRUSHED ALUMINIUM



ANODISED ALUM. (silver-gold) thermo packed
bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	H mm
PJAA 03 (anodised silver)	3
PJAO 03 (anodised gold)	3
PJAA 045 (anodised silver)	4,5
PJAO 045 (anodised gold)	4,5
PJAA 06 (anodised silver)	6
PJAO 06 (anodised gold)	6




POLISHED ALUMINIUM (chrome-gold) thermo packed
bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	H mm
PJBC 03 (polished chrome)	3
PJBO 03 (polished gold)	3
PJBC 045 (polished chrome)	4,5
PJBO 045 (polished gold)	4,5
PJBC 06 (polished chrome)	6
PJBO 06 (polished gold)	6

POLISHED BRUSHED ALUMINIUM (silver-copper-titanium) thermo packed
bar length 2,7 lm - pack 40 Pcs - 108 lm

Article	H mm
PJBS 03 (brushed silver)	3
PJRS 03 (brushed copper)	3
PJTS 03 (brushed titanium)	3
PJBS 045 (brushed silver)	4,5
PJRS 045 (brushed copper)	4,5
PJTS 045 (brushed titanium)	4,5

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROJOLLY" according to the tile thickness and desired finish. 2. Cut "PROJOLLY" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anchoring flange of "PROJOLLY" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

profiles for low thicknesses

COLOURS



* = On demand, price and delivery time to be agreed.