



PROTERMINAL

POLISHED AND SATIN FINISH STAINLESS STEEL
AISI 304/1.4301-V2A

profiles for low thicknesses



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



PROTERMINAL is a L-shaped profile in polished and satin finish stainless steel AISI 304/1.4301-V2A that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic and natural stone tiles, and also as separation profile for floor coverings. Its particular section and the availability in two different finishes make **PROTERMINAL** a much sought-after profile that allows a workmanlike application even in environments subject to high mechanical stresses.



1. Choose "PROTERMINAL" according to the tile thickness and desired finish.
2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROTERMINAL" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10mm

Article	H mm		
PTAC 03	3		
PTAC 045	4,5		
PTAC 06	6		

SATINED STAINLESS ST. AISI 304/1.4301-V2A with protective film
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 10/10mm


Article	H mm		
PTACS 03	3		
PTACS 045	4,5		
PTACS 06	6		

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.


PROTERMINAL

ANODIZED, POLISHED AND
BRUSHED ALUMINIUM

profiles for low thicknesses



EXAMPLES OF LAYING (for laying instructions see PROJOLLY)



1. Choose "PROTERMINAL" according to the tile thickness and desired finish.
2. Cut "PROTERMINAL" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROTERMINAL" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

COLOURS

ANODIZED			POLISHED		BRUSHED POLISHED		
AN - Natural aluminium	AA - Anodised silver alum.	AO - Anod. gold alum.	BC - Polished chrome alum.	BO - Polished gold alum.	BS - Brushed pol. silver aluminium	RS - Brushed copper alum.	TS - Brushed pol. titanium alum.

PROTERMINAL is a L-shaped profile in anodized aluminium that can be applied on external corners of coverings. It can be used to close the perimeter of coverings, like a connection profile between step tread and riser of stairs coated with ceramic or natural stone tiles and also as separation profile for floor and wall coverings. Its particular section and the availability in eight different finishes make **PROTERMINAL** a much sought-after profile that allows a workmanlike application.



POLISHED ALUMINIUM (chrome - gold) thermo packed

bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PTBC 03 (polished chrome)	3		
PTBO 03 (polished gold)	3		*
PTBC 045 (polished chrome)	4,5		
PTBO 045 (polished gold)	4,5		*
PTBC 06 (polished chrome)	6		
PTBO 06 (polished gold)	6		

NATURAL ALUMINIUM

bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PTAN 03 (naturale)	3		
PTAN 045 (naturale)	4,5		

ANODISED ALUMINIUM (silver-gold) thermo packed

bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PTAA 03 (anodised silver)	3		
PTAO 03 (anodised gold)	3		*
PTAA 045 (anodised silver)	4,5		
PTAO 045 (anodised gold)	4,5		*
PTAA 06 (anodised silver)	6		
PTAO 06 (anodised gold)	6		*

POLISHED BRUSHED ALUMINIUM (silver-copper-titanium)

thermo packed - bar length 2,7 lm - pack. 40 Pcs - 108 lm

Article	H mm		
PTBS 045 (brushed silver)	4,5		*
PTRS 045 (brushed copper)	4,5		*
PTTS 045 (brushed titanium)	4,5		*

* = On demand, price and delivery time to be agreed.