

**PROLISTEL ACC** is a listel in polished and satin finish stainless steel AISI 304/1.4301-V2A with a flat visible surface, suitable to decorate the wall coverings in ceramic, mosaic and natural stone. Its particular section and availability in four different finishes, make **PROLISTEL ACC** a much sought after profile. It can be used with the range of PROJOLLY profiles to decorate the wall coverings and to allow an elegant workmanlike application.

## PROLISTEL ACC

POLISHED AND SATIN FINISH STAINLESS STEEL AISI 304/1.4301-V2A



**POLISHED STAINLESS ST. AISI 304/1.4301-V2A with protective film**  
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	LxH mm		
PLTAC 1045	10 x 4,5		
PLTAC 2545	25 x 4,5		*

**SATINATED STAINLESS STEEL AISI 304/1.4301 V2A with protective film**  
bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	LxH mm		
PLTACS 1045	10 x 4,5		
PLTACS 2545	25 x 4,5		*

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS.

### COLOURS




AC - Polished stainless steel AISI 304/1.4301-V2A  
ACS - Satinated stainless steel AISI 304/1.4301-V2A

PLTAC/S 1045




PLTAC/S 2545



profiles for low thicknesses

### EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROLISTEL ACC" according to the width and desired finish.
2. Cut "PROLISTEL ACC" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROLISTEL ACC" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

**PROFINLIST 2045** is a listel in anodized, polished and brushed aluminium with a flat visible surface, suitable to decorate the wall coverings in ceramic and mosaic with low thickness. Its particular section and availability in four different finishes, make **PROFINLIST 2045** a much sought after profile. It can be used with the range of PROJOLLY profiles to decorate the wall coverings and to allow an elegant workmanlike application.

## PROFINLIST 2045

ANODIZED, POLISHED AND BRUSHED ALUMINIUM



**ANODISED SILVER ALUMINIUM thermo packed**

bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	H mm		
PFLTAA 2045	4,5		*

**POLISHED GOLD OR CHROMED ALUMINIUM thermo packed**

bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm

Article	H mm		
PFLTBC 2045	4,5		*
PFLTBO 2045	4,5		*

**BRUSHED POLISHED SILVER ALUMINIUM thermo packed**

bar length 2,7 lm - pack. 40 Pcs - 108 lm - 8/10mm


Article	H mm		
PFLTBS 2045	4,5		*

PFLT...2045



profiles for low thicknesses

### EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose "PROFINLIST 2045" according to the desired finish.
2. Cut "PROFINLIST 2045" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "PROFINLIST 2045" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.

### COLOURS



AA - Anodised silver alum. BC - Polished chrome alum. BO - Polished gold alum. BS - Brushed polished silver aluminium

\* = On demand, price and delivery time to be agreed.