
PROTOP

ANODIZED AND POLISHED ALUMINIUM

PROTOP is a rounded profile in anodized and polished aluminium. The profile protects the tile edges and decorates the countertops of kitckens realized with ceramic. Its particular section and elegance, the availability of three different finishes and special pieces such as internal and external corner at 90° and 135°, make **PROTOP** a much sought-after profile that allows an elegant workmanlike application.





COLOURS



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS

EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS

1. Choose "ROTO" according to the tile thickness and desired finish.

2. Cut "PROTOP" to the desired length and apply the adhesive on the support where the profile will be alid. 3. Press the anchoring flange of "PROTOP" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving, a 2 mm joint. Remove immediately literalism of adhesive from the surface of the profile. 5. Fill the joints between the profile leaving a thing pout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



ANODISED SILVER ALUMINIUM

but length 2,7 mm pacte. 101 G - 27 mm					
	Article	H mm			
	PCTAA 10	10			
	PCTAA 125	12.5			

POLISHED TITANIUM ALUMINIUM

ack 10 Prs - 27 Im

but tengen z,r ini pucit. To res z z ini			
Article	H mm		
PCTBT 10	10		
PCTBT 125	12,5		

POLISHED CHROME ALUMINIUM

bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article	H mm	
PCTBC 10	10	
PCTRC 125	12.5	

CORNERS

INTERNAL / EXTERNAL CORNERS ANODISED SILVER ALUMINIUM pack. 10 Pcs

Article	
EPCTAA 90 (external 90°)	
IPCTAA 90 (internal 90°)	
EPCTAA 135 (external 135°)	
IPCTAA 135 (internal 135°)	



Article	
EPCTBT 90 (external 90°)	
IPCTBT 90 (internal 90°)	
EPCTBT 135 (external 135°)	
IPCTBT 135 (internal 135°)	

INTERNAL / EXTERNAL CORNERS POLISHED CHROME ALUMINIUM nack 10 Pcs

Article	
EPCTBC 90 (external 90°)	
IPCTBC 90 (internal 90°)	
EPCTBC 135 (external 135°)	
IPCTBC 135 (internal 135°)	










PROTOP T

ANODIZED AND POLISHED ALUMINIUM

PROTOP T is a square profile in anodized and polished aluminium. The profile protects the tile edges and decorates the countertops of kitchens realized with ceramic. Its particular section and elegance, the availability of two different finishes and special pieces such as internal and external corner at 90° and 135°, make PROTOP T a much sought-after profile that allows an elegant workmanlike application.



EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS

EAAMPLE AND IN STATUTIONS FOR CATING METHODS.

1. Choose "PROTOP" according to the tile thickness and desired finish. 2. Cut"PROTOP" to the desired length and apply the adhesive on the support where the profile will be laid. 3. Press the anthoning flange of "PROTOP" into the adhesive. 4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile. 5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile. surface of the profile.



ANODISED SILVER ALUMINIUM bar length 2,7 lm - pack. 10 Pcs - 27 lm

Article PCTAA 10T 10 12.5

O PCTAA 125T

	POLISHED CHROME ALUMINIUM bar length 2,7 lm - pack. 10 Pcs - 27 lm			
	Article	H mm		
⊙	PCTBC 10T	10		
O	PCTBC 125T	12.5		

INTERNAL / EXTERNAL CORNER ANODISED CHROME ALUMINIUM pack. 10 Pcs

	Article	
③	IEPCTBC 12590T (90°)	
⊙	IEPCTBC 1090T (90°)	
③	IEPCTBC 10135T (135°)	
♠	IEPCTRC 125135T (135°)	



COLOURS



INTERNAL / EXTERNAL CORNER ANODISED SILVER ALUMINIUM pack. 10 Pcs

	Article	
②	IEPCTAA 12590T (90°)	
③	IEPCTAA 1090T (90°)	
②	IEPCTAA 10135T (135°)	
③	IEPCTAA 125135T (135°)	

