



## PROJOLLY SQUARE



### DESCRIPTION

**PROJOLLY SQUARE** is a square corner bead profile that can be applied on external corners of coverings. It can be used to close the perimeter of coverings. Its particular section and variety of colours, make **PROJOLLY SQUARE** an elegant and much sought after profile.

### MATERIAL

**PROJOLLY SQUARE** is a square corner bead profile in shockproof non - toxic colored vinyl resin available in the heights of 6 – 8 – 10 and 12.5 mm. It has a punched flange that guarantees a perfect grip to the adhesive. The high range of colours, combined with the availability of different heights and special pieces such as, internal and external corners, end caps and junctions, make **PROJOLLY SQUARE** an elegant and much sought after profile.

### AREAS OF USE

**PROJOLLY SQUARE** in shockproof non - toxic vinyl resin is suitable to be used for indoor walls.

### WARNINGS

Do not use **PROJOLLY SQUARE** in shockproof non - toxic vinyl resin outdoors. Do not clean it with substances that contain acetone and ethyl – butyl acetate (solvents).





### MAINTENANCE

**PROJOLLY SQUARE** does not require any special maintenance. It is suggested to clean it with normal household cleaning products.

### LAYING INSTRUCTIONS

1. Choose "**PROJOLLY SQUARE**" according to the tile thickness and desired colour.
2. Cut "**PROJOLLY SQUARE**" to the desired length and apply the adhesive on the support where the profile will be laid.
3. Press the anchoring flange of "**PROJOLLY SQUARE**" into the adhesive.
4. Lay the tiles, aligning them with the profile leaving a 2 mm joint. Remove immediately all remains of adhesive from the surface of the profile.
5. Fill the joints between the profile and the tiles with grout, in order to avoid water stagnation. Remove immediately all the remains of grout from the surface of the profile.



### TEXT TEMPLATE FOR TENDERS

Delivery and installation of a square corner bead profile in shockproof non - toxic vinyl resin in .... colour. With a height of ..... mm and equipped with a punched flange that guarantees a perfect grip to the adhesive, like PROJOLLY SQUARE of the Progress Profiles company.

**PJQ 06 / 08 / 10 / 125-...**: Shockproof non - toxic colored vinyl resin

Profile height : ..... mm  
Profile length : ..... mt  
Material : ..... €/mt  
Application : ..... €/mt  
Total value : ..... €/mt