

PROCANAL is a channel for joining floors and also for use as strips in wall coverings. This profile is made in natural, polished and chromed brass as well as natural or anodised silver aluminium. It is also used as a cable channel for the insertion of wires and conduits in all types of floor.

PROCANAL

NATURAL, POLISHED and CHROMED BRASS
NATURAL and ANODISED SILVER ALUMINIUM



NATURAL BRASS thermo packed 10 Pcs
POLISHED and CHROMED BRASS thermo packed
bar length 2,7 LM - packaging 40 Pcs - 108 LM (PCLOC 10 - 81 LM)

Article	W x H mm		
PCLOC 10 (natural)	10 x 10		
PCLOC 10 (polished)	10 x 10		
PCLOC 10 (chromed)	10 x 10		


Available Stainless steel AISI 304/1.4301-V2A
"PROLISTEL" 10x10 PLTAC 10 / PLTACS 10 (page 36)




NATURAL ALUMINIUM thermo packed 10 Pcs
ANODISED SILVER ALUMINIUM thermo packed
bar length 2,7 LM - packaging 40 Pcs - 108 LM

Article	W x H mm		
PCLAN 10 (natural)	10 x 10		
PCLAA 10 (anod. silver)	10 x 10		

PCL... 10




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose the profile in the required material and finish.
2. Apply the adhesive onto the area of application.
3. Lay the PROCANAL.
4. Continue laying by aligning it "flush" with the covering.
5. Use the adhesive to seal any empty interstices. Oxidation marks may be easily removed by polishing the profiles with specific products to be found on sale such as Sidel, Smac and similar.

COLOURS

(for a precise assessment of colours and finishes, see the relative enclosed sheet)



PROFLAT is a range of 20 and 40 mm natural brass or steel strips 3 mm thick. Ideal for dividing up flooring on the same level, they may be polished in situ and also curved/shaped to create decorative patterns that are particularly recommended for marble, Palladian, Venetian and cement or resin-based floors.

PROFLAT

STAINLESS STEEL AISI 304/1.4301-V2A
NATURAL BRASS



STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2 LM - packaging 15 Pcs - 30 LM

Article	W x H mm		
GPLAC 2032	3 x 20		
GPLAC 4032	3 x 40		

STAINLESS STEEL AISI 304/1.4301-V2A
bar length 4 LM - packaging 15 Pcs - 60 LM

Article	W x H mm		
GPLAC 2034	3 x 20		
GPLAC 4034	3 x 40		

STAINLESS STEEL AISI 304/1.4301-V2A
bar length 2 / 4 LM - packaging 15 Pcs

Article	W x H mm		
GPLAC 2052	5 x 20		
GPLAC 5052	5 x 50		
GPLAC 2054	5 x 20		
GPLAC 5054	5 x 50		

AVAILABLE ON REQUEST IN SATINED STAINLESS STEEL

SUITABLE FOR USE IN CONTACT WITH FOODSTUFFS


* = Upon request, price and delivery time to be agreed.




POLISHABLE NATURAL BRASS
bar length 2,7 LM - packaging 15 Pcs - 40,5 LM

Article	W x H mm		
GPLON 2025	2,5 x 20		
GPLON 4025	2,5 x 40		


GPLAC 203. / 205..




GPLON 2025




GPLAC 403. / 505..



GPLON 4025




EXAMPLES AND INSTRUCTIONS FOR LAYING METHODS



1. Choose PROFLAT with the same height as the thickness of the floor.
2. Cut the profile to the necessary length and place it along the edge of the laid floor or insert it from above.
3. Continue the laying "flush" with the PROFLAT.

COLOURS



(for a precise assessment of colours and finishes, see the relative enclosed sheet)